

Thank you for selecting a WeatherBeater® Floor Liner from Winfield Consumer Products. Your new third seat liner is custom molded to fit your Dodge Durango. The liner is made to take the place of your factory floor mats. *For correct fit, it is necessary to remove the factory floor mats before installing your new floor liners*. *However, do not remove the factory-installed carpeting.*

Your liner is made from an engineering resin that is lightweight and extremely tough and durable. The easiest way to clean your liner is with a damp cloth or sponge. If using a cleaner, 409[®] or Glass Plus[®] work well. Use of Armor All[®], Son-of-a-Gun[®] or similar items is discouraged as these products make the liner slick.

INSTALLATION INSTRUCTIONS FOR YOUR DODGE DURANGO THIRD SEAT FLOOR LINER

BACK OF VEHICLE



TO INSTALL YOUR NEW THIRD SEAT FLOOR LINER, YOU MUST FIRST FOLD AND FLIP FORWARD YOUR SECOND ROW OF SEATS TO ALLOW ACCESS TO THE THIRD ROW FLOOR PAN. WITH THIS DONE, INSTALL THE LINER AS SHOWN IN THE DIAGRAM ABOVE. NOTE THAT BOTH SECOND ROW SEATS WILL FASTEN THROUGH THE TRIMMED AREA IN THE LINER WHEN THEY ARE FOLDED BACK INTO THE NORMAL USE POSITION. IF YOUR LINER DOES NOT HAVE THE TRIM AREA REMOVED, DO NOT INSTALL THE LINER AS YOUR 2ND ROW SEATS WILL NOT FASTEN SECURELY INTO PLACE. INSTEAD, PLEASE CALL HUSKY LINERS AT 800-344-8759.